

Let us

# Perfect

your water and

# Maximize

your peace of mind.

## ETF2300AIV & EIV

**ECOWATER SERIES – AIR ASPIRATED FILTERS** 

## Eliminate Problem Water for Good

### Air Aspirated Chemical Free Filter

Chemical free system is clean and economical, using air instead of bleach, chlorine or potassium permanganate. Fresh air provides oxidation.

1 Electronic Timer Controls with HydroLink Plus® Wi-Fi and Smartphone App Monitoring

Wi-Fi enabled technology sends continuous and excessive water use, system error and service reminder alerts.

#### Water Meter

Allowing for chemical feed dosing, flow switch operation and water use information.

- 2 Naturally Aspirated Air Induction Air is drawn into mineral tank for oxidation, no pumps or chemicals.
- 3 Multi-Wrap Fiberglass Reinforced Media Tank Durable fiberglass-wrapped tank liner – doesn't deteriorate, rust, or corrode.
- Full One-Inch Riser
  One-inch diameter for increased flow rates, which ensures that household demand is adequately met.

Multi-Cycle Valve with Easy-Clamp Ring and Patented Coated Disc

- Models ETF2300AIV 10" & 12" Ship with Zeolite Media for Iron Removal Models ETF2300EIV 10" & 12" Ship Without Media, Allowing for Loading Media of Choice
- Washed Quartz Underbedding
  Washed quartz underbedding aids in dispersion of water throughout the media tank.





# ETF2300AIV & EIV

# ECOWATER SERIES <u>AIR ASPIRATED</u> FILTERS

### **DIMENSIONS**



		ETF2300 AIV10	ETF2300 AIV12	ETF2300 EIV10	ETF2300 EIV12
-	Nominal Resin Tank Size	10" Diam. x 47"	12" Diam. x 54"	10" Diam. x 47"	12" Diam. x 54"
	А	57"	62.5"	57"	62.5"
	В	50"	55.75"	50"	55.75"

### **SPECIFICATIONS**

	ETF2300AIV10	ETF2300AIV12	ETF2300EIV10 <sup>3</sup>	ETF2300EIV124
Maximum Clear or Red Iron* Removal (ppm) <sup>1</sup>	10	10	_	-
Maximum Water Pressure (psi)	80	80	80	80
Supply Water Temperature Limits (°F/C°)¹	4 -120/4 - 49	4 -120/4 - 49	120/49	120/49
Maximum Flow Rate (gpm)	7 – 10	9 – 15	_	_
Minimum Backwash Flow Rate (gpm) <sup>2</sup>	<b>7</b> <sup>2</sup>	10 <sup>2</sup>	_	_

Electrical Requirement, 120V, 50/60Hz, (24V DC, 500 mA, power supply included)

#### WARRANTY

- For the lifetime of the original owner, the mineral tank will not rust, corrode, leak, burst, or in any other manner fail to perform it's proper function.
- For a period of five years, the valve body will be free of defects in materials and workmanship and will perform it's proper function.
- For a period of seven years, the electronic faceplate will be free of defects in materials and workmanship and will perform it's normal function.
- For a period of one year, all other parts will be free of defects in materials and workmanship and will perform their normal functions.














MS2







<sup>\*</sup>Except, bacterial and organically bound iron.

¹Actual performance may vary depending on local water conditions. ²Well pump must be able to provide the minimum flow for 30+ minutes. ³System is shipped with gravel only, no media. Can be loaded with media of customer's choice. System is shipped with 10" x 47" mineral tank and 7 gpm backwash flow control. Follow media manufacturer's recommendation for application and backwash flow rates.

<sup>&</sup>quot;System is shipped with gravel only, no media. Can be loaded with media of customer's choice. System is shipped with 12" x 54" mineral tank and 10 gpm backwash flow control. Follow media manufacturer's recommendation for application and backwash flow rates.